

PRODUCT SPECIFICATIONS CH/VTB/PROHEAT 18



CH 18 CH 12 CH 3



Proheat 18



VTB 15000/18000 VTB 9000 VTB 3000

TECHNICAL SPECIFICATIONS | DIMENSIONS AND WEIGHTS

1 kW = 860 kcal/h 1 kW = 3,413 Btu/h 1 kW = 3.6 MJ/h 1 kg = 1.2 l/h

MODEL	Proheat 18	VTB 3000	VTB 9000	VTB 15000	VTB 18000	CH 3	CH 12	CH 18
Item number	40.018.000	40.107.030	40.107.035	40.107.025	40.107.040	40.107.091	40.107.092	40.107.093
Heat output (Btu/hr)	61,000	9,560	31,000	51,000	61,000	10,000	41,000	61,000
Heat output (kW)	18	3	9	15	18	3	12	18
Adjustment range (kW)	0-9-18	0-3	0-4.5-9	0-6-9-15	0-9-18	0-3	0-6-9-12	0-9-13.5-18
Power supply (V)	3x400	230	3x400	3x400	3x400	230	3x400	3x400
Power consumption (AMPS)	13-26	13	11.5-13	8-14-23	14-26	13	18	26
Delta T (°C)	120	60	100	38-60-100	70-110	60	100	90
Heated air flow (m³/hr)	1.000	225	550	1.000	1.000	250	600	1.500
230 volt plug		*				*		
400 volt 16 Amp plug			*					
400 volt 32 Amp plug	*			*	*		*	*
Radial fan	*	*	*	*	*			
Axial fan						*	*	*
Outlet cone Ø (mm)		98	120	150	150	160	300	300
Hose connector		*	*	*	*	*	*	*
Thermostat built-in	*	*	*	*	*			
Thermostat connection	*					*	*	*
Hand grip		*	*			*	*	*
Wheels	*			*	*			
Dim. heater only LxWxH (cm)	51x40x97	40x34x31	68x34x31	86x48x52	86x48x52	38x28x39	66x37x45	55x43x58
Dim. incl. packing LxWxH (cm)	107x70x57	45x36x35	72x36x35	102x46x51	102x46x51	38x28x38	65x37x45	55x42x58
Weight (kg)	40	11	18	33	33	11	23	28
Weight incl. packing (kg)	53	12	21	39	39	13	25	30

ACCESSOIRES

MODEL	Proheat 18	VTB 3000	VTB 9000	VTB 15000	VTB 18000	CH 3	CH 12	CH 18	Item number
THERMOSTATS									
RT1, room thermostat -10/+40 °C with 5 m cable and plug, IP 54, switching differential ± 2 degrees.	*								40.228.405
RT2, as RT1, with 10 m cable IP 54.	*								40.228.410
RT3, as RT1, with 20 m cable IP 54.	*								40.228.420
Extension cable 10 m for thermostat, with plug.	*								40.202.140
Thermostat for CH							*	*	40.107.098
Fault detector GSM room temperature monitoring, no connections needed. Regardless of the type of heater.	*	*	*	*	*	*	*	*	40.223.400
WARM AIR TRANSPORT HOSES									
		Ø (mm)							
Temperature resistant -40/+140 °C grey, L = 5 m		100	*						40.107.270
		120		*					40.107.275
		150			*	*			40.107.071
		300					*	*	40.107.077



RT1, RT2, RT3



Thermostat for CH 12/18



GSM fault detector



Grey hose

THERMOBILE INDUSTRIES BV

Konijnenberg 80 - 4825 BD Breda - Postbus 3312 - 4800 DH Breda - The Netherlands - T + 31 76 587 34 50 - F + 31 76 587 27 89
 sales@thermobile.com - www.thermobile.com - Chamber of Commerce: Breda 20120375 - VAT nr.: NL 8146.04.365 B01